

**Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Currently amended) A system comprising:  
a processor;  
a sensor interface responsive to the processor and configured to receive environmental data; and  
memory responsive to the processor, the memory including: program instructions operable to direct the processor to implement a kernel-mode device driver for manipulating a journal based data system associated with data received via the sensor interface.
2. (Original) The system of claim 1, wherein the kernel-mode device driver runs with supervisor privilege within a kernel of an operating system.
3. (Original) The system of claim 1, wherein the kernel-mode device driver comprises code that runs with kernel privilege and provides access to a hardware device.
4. (Original) The system of claim 1, wherein the memory further comprises program instructions for implementing a monitoring application.
5. (Original) The system of claim 1, further comprising a network interface responsive to the processor.
6. (Original) The system of claim 5, wherein the memory further comprises program instructions for implementing a notification application for communicating data events via the network interface.

7. (Original) The system of claim 5, wherein the memory further comprises program instructions for implementing a web server for communicating data via the network interface.

8. (Currently amended) The system of claim 1, wherein the memory further comprises program instructions for implementing a plurality of variable definitions in the journal based data system~~includes a plurality of variable definitions~~.

9. (Currently amended) The system of claim 8, wherein the memory further comprises program instructions for implementing each variable definition of the plurality of variable definitions ~~has~~ to have an associated variable and ~~includes~~ to include an oldest update field and a latest update field.

10. (Currently amended) The system of claim 1, wherein the memory further comprises program instructions for implementing a plurality of variable update records in the journal based data system~~includes a plurality of update records~~.

11. (Currently amended) The system of claim 10, wherein the memory further comprises program instructions for implementing each variable update record of the plurality of variable update records ~~has~~ to have an associated variable and ~~includes~~ to include a variable value, a next update pointer, and a previous update pointer.

12. (Currently amended) The system of claim 11, wherein the memory further comprises program instructions for implementing the previous update pointer ~~points to point~~ to point to an oldest update field of a variable definition associated with the associated variable.

13. (Currently amended) The system of claim 11, wherein the memory further comprises program instructions for implementing the next update pointer ~~points to point~~ to point to the latest update field of a variable definition associated with the associated variable.

14. (Currently amended) The system of claim 1, wherein the memory further comprises program instructions for implementing a context record in the journal based data system~~includes a context record.~~

15. (Currently amended) The system of claim 14, wherein the memory further comprises program instructions for implementing a current timestamp field in the context record~~includes a current timestamp field.~~

16. (Currently amended) The system of claim 14, wherein the memory further comprises program instructions for implementing, in the context record~~includes,~~ a next update field including a pointer to a next update in a global journal of update records.

17. (Withdrawn) A system for maintaining data integrity, the system comprising:  
memory including: a plurality of variable definitions, each variable definition of the plurality of variable definitions having an associated variable and including an oldest update field and a latest update field;

a plurality of variable update records, each variable update record having an associated variable and including a variable value, a next update pointer, and a previous update pointer, the previous update pointer of a first variable update record associated with one variable pointing to the oldest update field of a variable definition associated with the one variable, the next update pointer of a second variable update record associated with the one variable pointing to the latest update field of the variable definition associated with the one variable; and

a plurality of context records, each context record of the plurality of context records having an associated current timestamp field and a context update field pointing to a third variable update record of the plurality of variable update records.

18. (Withdrawn) The system of claim 17, wherein each variable definition further comprises an identification string, and the system further comprising a hash table with records hashed by the identification string.

19. (Withdrawn) The system of claim 17, wherein each variable definition further comprises a class pointer, the class pointer indicating a class and permitting inheritance of class attributes.
20. (Withdrawn) The system of claim 17, wherein each variable definition further comprises a creation timestamp.
21. (Withdrawn) The system of claim 17, wherein each variable definition further comprises a flag.
22. (Withdrawn) The system of claim 21, wherein the flag indicates an attribute selected from the group consisting of a read-only flag, a constant flag, and an undeletable flag.
23. (Withdrawn) The system of claim 21, wherein the flag indicates a persistence attribute.
24. (Withdrawn) The system of claim 17, wherein each variable update record comprises a variable update timestamp.
25. (Withdrawn) The system of claim 17, wherein each of the plurality of variable update records that have a timestamp older than the current timestamp of a context record having the oldest current timestamp of the plurality of context records are discarded.
26. (Withdrawn) A method for accessing a value associated with a variable at a target time, the method comprising:
- searching a variable record table for a variable record, the variable record having a variable identification associated with the variable, a latest update pointer, a creation time not greater than the target time, and a latest update time; and
  - selectively searching a set of update records starting with a first update record indicated by the latest update pointer and following a previous update pointer included in the first update record to a subsequent update record.

27. (Withdrawn) The method of claim 26, wherein the update record is an oldest update record stored in the variable record.
28. (Withdrawn) The method of claim 26, wherein the target time is associated with a context record.
29. (Withdrawn) The method of claim 26, further comprising comparing the value to a threshold.
30. (Withdrawn) The method of claim 26, further comprising transmitting the value via a network.
31. (Withdrawn) The method of claim 26, further comprising incorporating the value into an XML document.
32. (Withdrawn) A method for managing memory, the method comprising:  
determining an oldest timestamp of interest; searching a set of update records starting at a specified start point and proceeding chronologically to subsequent update records until identifying a first update record with a timestamp newer than the oldest timestamp of interest;  
setting the specified start point to the record chronologically following the first update record; and  
revising a variable record associated with the first update record.
33. (Withdrawn) The method of claim 32, wherein revising the variable record comprises: copying contents of the first update record into an oldest record associated with the variable record; and removing the first update record from the set of update records.
34. (Withdrawn) The method of claim 32, wherein revising the variable record comprises: determining if the update record is the oldest update record for an associated variable and

whether a value of the update record has been deleted; and selectively, unlinking the variable record from a variable table.

35. (Withdrawn) The method of claim 32, wherein the oldest timestamp of interest is associated with a context record.

36. (New) A method for processing data from a sensor comprising:  
storing, in memory, program instructions operable to direct a processor to implement a kernel-mode device driver;  
executing, by a processor, the program instructions implementing the kernel-mode device driver;  
receiving, by the implemented kernel-mode device driver, environmental data via a sensor interface; and  
manipulating a journal based data system associated with the environmental data.

37. (New) The method of claim 36, wherein executing, by the processor, the program instructions implementing the kernel-mode device driver comprises implementing a kernel-mode device driver that executes with supervisor privilege within a kernel of an operating system.

38. (New) The method of claim 36, further comprising storing, in the memory, program instructions for implementing a monitoring application.

39. (New) A computer readable medium having computer readable signals stored thereon that define instructions that, as a result of being executed by a computer, instruct the computer to perform a method for extracting meaning from a plurality of documents, the method comprising:  
storing program instructions operable to direct a processor to implement a kernel-mode device driver;  
executing, by a processor, the program instructions;  
receiving, by the executing kernel-mode device driver, environmental data via a sensor interface; and

manipulating a journal based data system associated with the environmental data.